

### Standard O-ring Sizes

Standard O-ring Sizes (900 series)

AS 568A Uniform	Tube O.D. (Ref)	O-ring Size - Actual (b) per AS568A (Units are in inches)				Metric O-ring Size per AS568A (b) (Units are in millimeters)			
		Tolerance (C)				Tolerance (C)			
Dash No.		I.D.	±	W	±	I.D.	±	W	±
-901	3/32	.185	.005	.056	.003	4,70	0,13	1,42	0,08
-902	1/8	.239	.005	.064	.003	6,07	0,13	1,63	0,08
-903	3/16	.301	.005	.064	.003	7,65	0,13	1,63	0,08
-904	1/4	.351	.005	.072	.003	8,92	0,13	1,83	0,08
-905	5/16	.414	.005	.072	.003	10,52	0,13	1,83	0,08
-906	3/8	.468	.005	.078	.003	11,89	0,13	1,98	0,08
-907	7/16	.530	.007	.082	.003	13,46	0,18	2,08	0,08
-908	1/2	.644	.009	.087	.003	16,36	0,23	2,21	0,08
-909	9/16	.706	.009	.097	.003	17,93	0,23	2,46	0,08
-910	5/8	.755	.009	.097	.003	19,18	0,23	2,46	0,08
-911	11/16	.863	.009	.116	.004	21,92	0,23	2,95	0,10
-912	3/4	.924	.009	.116	.004	23,47	0,23	2,95	0,10
-913	13/16	.986	.010	.116	.004	25,04	0,26	2,95	0,10
-914	7/8	1.047	.010	.116	.004	26,59	0,26	2,95	0,10
-916	1	1.171	.010	.116	.004	29,74	0,26	2,95	0,10
-918	1- 1/8	1.355	.012	.116	.004	34,42	0,30	2,95	0,10
-920	1- 1/4	1.475	.014	.118	.004	37,47	0,36	3,00	0,10
-924	1- 1/2	1.720	.014	.118	.004	43,69	0,36	3,00	0,10
-928	1- 3/4	2.090	.018	.118	.004	53,09	0,46	3,00	0,10
-932	2	2.337	.018	.118	.004	59,36	0,46	3,00	0,10

These O-rings are intended for use with internal straight thread fluid connection bosses and tube fittings.

Ref. AND10049, AND10050, MS33656, MS33657, SAE straight thread O-ring boss and mating swivel and adjustable style fittings.